

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, Daisuke Kitazawa, a citizen of Japan residing at 21-26-203 Noukendai-dori, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0053 Japan, Hijin Sato, a citizen of Japan residing at 1-36-4 Kounandai, Kounan-ku, Yokohama-shi, Kanagawa 234-0054 Japan and Narumi Umeda, a citizen of Japan, residing at 6-40-14 Tomioka-nishi, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0052 Japan have invented certain new and useful improvements in

METHOD FOR ALLOCATING RADIO RESOURCE, RADIO  
COMMUNICATION APPARATUS AND RADIO  
COMMUNICATION SYSTEM

of which the following is a specification:-

TITLE OF THE INVENTION

METHOD FOR ALLOCATING RADIO RESOURCE,  
RADIO COMMUNICATION APPARATUS AND RADIO COMMUNICATION  
SYSTEM

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to  
methods for allocating radio resource, radio  
10 communication apparatuses and a radio communication  
system, and more particularly to a method for  
allocating radio resource, a radio communication  
apparatus and the radio communication system in which  
radio resource is allocated for a terminal or a  
15 communication connection.

2. Description of the Related Art

In a conventional radio communication  
system in which a conventional voice media was a core  
of communication connections, when control for  
20 improving in a use effectiveness of the radio  
resource was performed, the radio communication  
system controlled to maintain a fairness of a  
communication quality in all terminals. In the  
conventional radio communication system, it could be  
25 thought that the communication quality was equal to  
all terminals. However, recently, users demand to  
download various media such as not only voice media  
but also non-voice data communication, a dynamic  
image or static image, so called multimedia has been  
30 increasing. It is becoming essential for a future  
radio communications system to provide such various  
multimedia services.

In order to provide these multimedia  
services as users are sufficiently satisfied, it is  
35 thought that it is necessary to set communication  
quality as a different value for each terminal or  
each communication connection. For example, it is

095856 100101

required for one communication connection conducting a voice communication to be as few transit-delay time as possible even if a tone quality is somewhat degraded. On the other hand, it is required for another communication connection conducting a data communication to have less data errors while a transit-delay time is allowed to be greater. Accordingly, when the radio communication system provides various multimedia services, as well as a system design conducting an effective transmission effectively using radio resource, a control is required to satisfy a communication quality needed by each of terminals or communication connection handling different media.

In a conventional technology, various designs have been made for the control in the radio communication system conducts such multimedia service. However, the communication quality is different for each terminal or each communication connection, a proper control cannot be conducted to satisfy the communication quality required by each terminal or each communication connection. Such problems in the conventional technologies will now be described with reference to FIG.1 and FIG.2.

FIG.1 is a diagram showing a relationship between a reference value and an actual value in a case in which the conventional radio communication system unitary determines the reference value of required communication quality for all terminals. In this case, it is assumed that one terminal establishes a communication connection for one medium.

In the conventional technology, when radio resource is allocated for each terminal, a terminal, which communication quality is degraded lower than required communication quality, is prioritized and then it is controlled so that the radio resource is allocated in a lower order of the communication

(5)

15

30

5 B and the terminal A satisfying the required quality is prioritized higher than the terminal B that does not satisfy the required quality. In addition, when the terminal C is compared with the terminal D, the terminal C is much lower than the requested quality and then the terminal C should be prioritized higher than the terminal D. However, in the conventional radio resource allocating process, the terminal D is prioritized higher than the terminal C.

10 As described above, the conventional radio resource allocating process simply allocates the radio resource in the low order of the communication quality. Alternatively, the conventional radio resource allocation process prioritizes terminals  
15 which communication qualities are lower than a fixed or unitarily reference value of the radio communication system, and then allocates the radio resource to the terminals in the low order of the communication qualities. Either one of these  
20 conventional radio resource allocating processes is an effective allocating process only in a case in which all terminals or all communication connections require the same communication quality. However, in a radio communication system for multimedia, each  
25 terminal or each communication connection requires a different communication quality. Thus, when the radio resource is allocated in the order like the conventional radio resource allocating processes, the number of the terminals or the communication  
30 connections that do not satisfy the required quality is increased in a case there is no sufficient radio resource.

#### SUMMARY OF THE INVENTION

35 It is a general object of the present invention to provide a method for allocating radio resource, a radio communication apparatus and a radio

09565856 100101

communication system in which the above-mentioned problems are eliminated.

5 A more specific object of the present invention is to provide the method for allocating radio resource, the radio communication apparatus and the radio communication system which the number of terminals or communication connections satisfying respective required qualities can be increased.

10 The above objects of the present invention are achieved by a method for allocating radio resource to radio terminals or communication connections in a radio communication system in which each of the radio terminals or communication connections requires a different communication  
15 quality, the method including the steps of: (a) retrieving a first group including radio terminals or communication connections in which actual communication qualities are degraded more than required communication qualities, and a second group  
20 including radio terminals or communication connections in which actual communication qualities are favorable more than required communication qualities; and (b) allocating the radio resource to the radio terminals or communication connections in  
25 the first group with higher priority than the radio terminals or communication connections in the second group.

According to the present invention, instead of conventionally allocating the radio  
30 resource based on only the actual communication qualities without considering the required communication qualities by the radio terminals or communication connections, the radio resource is allocated to the radio terminals or communication  
35 connections in which the actual communication qualities are degraded more than the required qualities, with higher priority than the radio

00965856 100101

terminals or communication connections in which the actual communication qualities are favorable more than the required qualities. Therefore, it is possible to improve the actual communication

5 qualities of the radio terminals or communication connections with higher priority. The radio resource can be the time slot in time-division multiple access method, the frequency band in frequency-division-multiplex access method, the diffusion code in code-

10 division-multiple-access method, or transmitted electric power of the radio base station or the radio terminals.

The above objects of the present invention are achieved by a radio communication apparatus for

15 allocating radio resource to radio terminals or communication connections in a radio communication system in which each of the radio terminals or communication connections requires a different communication quality, the radio communication

20 apparatus including: a first retrieving part retrieving a first group including radio terminals or communication connections in which actual communication qualities are degraded more than required communication qualities, and a second group

25 including radio terminals or communication connections in which actual communication qualities are favorable more than required communication qualities; and a first allocating part allocating the radio resource to the radio terminals or

30 communication connections in the first group with higher priority than the radio terminals or communication connections in the second group.

According to the present invention, it is possible to provide the radio communication apparatus

35 that is suitable for the above-described method for allocating radio resource to radio terminals or communication connections.

09965856 100101

The above objects of the present invention are achieved by a radio communication system which allocates radio resource for a radio communication, the radio communication system including a radio communication apparatus and radio terminals, wherein each of the radio terminals includes a requiring part requiring a different communication quality to the radio communication system for each radio terminal or communication connection, and the radio communication apparatus including: a first retrieving part retrieving a first group including radio terminals or communication connections in which actual communication qualities are degraded more than required communication qualities, and a second group including radio terminals or communication connections in which actual communication qualities are favorable more than required communication qualities; and a first allocating part allocating the radio resource to the radio terminals or communication connections in the first group with higher priority than the radio terminals or communication connections in the second group.

According to the present invention, it is possible to provide the radio communication system that is suitable for the above-described method for allocating radio resource to radio terminals or communication connections.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings, in which:

FIG.1 is a diagram showing a relationship between a reference value and an actual value in a case in which a conventional radio communication system unitary determines a reference value of

required communication quality for all terminals;

FIG.2 is a diagram showing a relationship between the required communication quality and actual communication quality in a case in which each  
5 terminal individually requires a necessary communication quality;

FIG.3 is a diagram showing basic configuration of a radio communication system applying radio resource allocating method and a radio  
10 communication apparatus according to the embodiment of the present invention;

FIG.4 is a block diagram showing a radio base station applying the radio communication apparatus according to the embodiment of the present  
15 invention;

FIG.5 is a flowchart for explaining the radio resource allocating process based on required quality of each of the radio terminals or communication connections;

FIG.6 is a flowchart for explaining a  
20 first radio resource allocating process in a low order of actual communication qualities;

FIG.7 is a flowchart for explaining a second radio resource allocating process for  
25 allocating the radio resource to unsatisfied radio terminals or communication connections in a descending order of differences between the required qualities and the actual communication qualities;

FIG.8 is a flowchart for explaining a  
30 third radio resource allocating process for allocating the radio resource to satisfied radio terminals or communication connections in an ascending order of a difference between the required quality and the actual communication quality;

FIG.9 is a flowchart for explaining a  
35 fourth radio resource allocating process for allocating the radio resource to the unsatisfied

09965856-100101

radio terminals or communication connections in an descending order of a degradation degree of the actual communication quality to the required quality;

FIG.10 is a flowchart for explaining a fifth radio resource allocating process for allocating the radio resource to the satisfied radio terminals or communication connections in an ascending order of a favorable degree of the actual communication quality to the required quality;

FIG.11 is a flowchart for explaining a sixth radio resource allocating process in a case in which quality-required radio terminals or communication connections and quality-not-required radio terminals or communication connections are managed by the same radio base station:

FIG.12 is a diagram showing an allowable delay time and an actual delay time for each radio terminal in a case in which the required quality is the allowable delay time.

FIG.13 is a diagram showing a state distinguishing radio terminals that satisfy the required qualities and that do not satisfy the required qualities in FIG.10;

FIG.14 is a diagram showing a required throughput and an actual throughput for each radio terminal in a case in which the required quality is a throughput; and

FIG.15 is a diagram showing a state distinguishing radio terminals that satisfy the required qualities and that do not satisfy the required qualities in FIG.12.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment according to the present invention will now be described with reference to figures. FIG.3 is a diagram showing basic configuration of the radio communication system

0995856-100101

applying the radio resource allocating method and a radio communication apparatus according to the embodiment of the present invention.

In FIG.3, one radio base station 1 manages a plurality of radio terminals 10, 20, 30 and 40. That is, all of the plurality of radio terminals 10, 20, 30 and 40 communicate the same radio base station 1 and the radio base station 1 allocates the radio resource such as a time slot in time-division multiple access method, a frequency band in frequency-division-multiplex access method, a diffusion code in code-division-multiple-access method, transmitted electric power of the radio base station 1 or the radio terminals 10 through 40, or a like, for each of the radio terminals 10 through 40 or each communication connection between the radio base station 1 and the radio terminals 10 through 40.

In FIG.3, for example, the radio terminal 10 receives image data from the radio base station 1 and the radio terminal 20 transmits picture data taken with a camera. Also, the terminal 30 transmits data by a personal computer and the terminal 40 conducts voice communications with another radio terminal located in a remote area. When the radio communication system is such a system for multimedia communications, each of the radio terminals 10 through 40 or each communication connection requires a different communication quality (required quality).

In addition, the radio base station 1 includes buffers 11, 21, 31 and 41 for the number of the radio terminals 10 through 40 that are to be connected to the radio base station 1. The buffer 11 stores packets to transmit to the radio terminal 10. Similarly, the buffers 21 through 41 store packets to transmit to the radio terminals 20 through 40, respectively. On the other hand, each of the radio terminals 10 through 40 are provided with buffers 12,

09065856 100101

22, 32 and 42, respectively, to store packets to transmit to the radio base station 1.

FIG.4 is a block diagram showing the radio base station applying the radio communication apparatus according to the embodiment of the present invention. In this case, the required quality for each of the radio terminals 10 through 40 or each communication connection is an allowable delay time, a transmission rate, a throughput or a like. In order to determine a priority order for radio resource allocation, the radio base station 1 executes a communication quality measuring part 106 and then the communication quality measuring part 106 measures the communication quality for each of the radio terminals 10 through 40 or each communication connection at that time based on information sent from a receiver 102 or a transmitter 104.

After the communication quality is measured, the radio base station 1 executes a resource allocation priority ordering part 108 and then the resource allocation priority ordering part 108 determines the priority order for the radio resource allocation by a method that will be described later, based on a measured communication quality and the required quality reported from each of the radio terminals 10 through 40 or each communication connection beforehand. Subsequently, a resource allocating part 110 allocates the radio resource for each of the radio terminals 10 through 40 or each communication connection based on the priority order determined by the resource allocation priority ordering part 108 and then data is received and transmitted.

FIG.5 is a flowchart for explaining the radio resource allocating process based on the required quality of each of the radio terminals 10 through 40 or each communication connection. The

09065856 100101

resource allocation priority ordering part 108  
determines for all radio terminals 10 through 40 or  
all communication connections whether or not an  
actual communication quality satisfies the required  
5 quality (step 301).

After this determination process, the  
resource allocation priority ordering part 108  
determines the priority order so as to allocate the  
radio resource to unsatisfied radio terminals or  
10 communication connections, which do not satisfy  
respective required qualities, with higher priorities  
than satisfied radio terminals or satisfied  
communication connections, which satisfy respective  
required qualities. First, the radio resource  
15 allocating process with a higher priority is  
conducted for the unsatisfied radio terminals or  
communication connections (step 302). Next, it is  
determined whether or not the radio resource is  
remaining (step 303). When the radio resource is  
20 remaining, the radio resource allocating process is  
conducted for the unsatisfied radio terminals or  
communication connections (step 304).

As described above, since the radio  
resource allocating process considering the required  
25 quality is conducted, the radio resource is allocated  
to the unsatisfied radio terminals or communication  
connections with higher priority even if the actual  
communication qualities thereof are better than that  
of the satisfied radio terminals or the satisfied  
30 communication connections.

There are various methods for determining  
the priority order for the radio resource allocation  
in the radio resource allocating process for the  
unsatisfied radio terminals or communication  
35 connections (step 302) shown in FIG.5 and another  
radio resource allocating process for the satisfied  
radio terminals or the satisfied communication

0965856 100101

connections (step 304) shown in FIG.5. Details of the methods will now be described with reference to flowcharts shown in FIG.6 through FIG.10.

FIG.6 is a flowchart for explaining a  
5 first radio resource allocating process in the low order of actual communication qualities. First, the resource allocation priority ordering part 108 sorts all radio terminals or all communication connections that do not satisfy respective required qualities in  
10 the low order of the actual communication qualities (step 401). A sorted order becomes the priority order of the radio resource allocation.

When the priority order of the radio resource allocation is determined, the resource  
15 allocating part 110 determines whether or not the radio resource is remaining (step 402). When the radio resource is remaining, the remained radio resource is allocated to the unsatisfied radio terminals or communication connections (step 403).  
20 On the other hand, when the radio resource is not remained, the second radio resource allocating process is terminated.

The determination process for determining whether or not the radio resource is remaining (step  
25 402) and the radio resource allocating process (step 403) are repeated until the radio resource is allocated to all unsatisfied radio terminals or all unsatisfied communication connection that do not satisfy respective required quality, or until there  
30 is no radio resource available to allocate. Thus, by allocating radio resource in the low order of the actual communication quality, it is possible to improve greatly degraded communication qualities with higher priority.

35 In FIG.6, the case of allocating the radio resource to the unsatisfied radio terminals and the unsatisfied communication connections is described.

00005555 100101

Also, the radio resource can be allocated to the satisfied radio terminals or the satisfied communication connections.

FIG.7 is a flowchart for explaining a  
5 second radio resource allocating process for  
allocating the radio resource to the unsatisfied  
radio terminals or communication connections in a  
descending order of differences between the required  
qualities and the actual communication qualities.  
10 First, the resource allocation priority ordering part  
108 sorts all unsatisfied radio terminals or  
communication connections in the descending order  
(greater to smaller) of a value that deducted the  
actual communication quality from the required  
15 quality (step 501). The sorted order becomes the  
priority order of the radio resource allocation.

When the priority order of the radio  
resource allocation is determined, the resource  
allocating part 110 determines whether or not the  
20 radio resource is remaining (step 502). When the  
radio resource is remaining, the remained radio  
resource is allocated to the unsatisfied radio  
terminals or communication connections (step 503).  
On the other hand, when the radio resource is not  
25 remained, the second radio resource allocating  
process is terminated. Thus, by allocating the radio  
resource in the descending order of the value that  
deducted the actual communication quality from the  
required quality, it is possible to improve greatly  
30 degraded communication qualities with higher priority.

For example, it is assumed that the  
communication quality is shown by the delay time at a  
transmission and the required qualities of the radio  
terminals or the communication connections are shown  
35 by an allowable delay time. Also, it is assumed that  
there are a radio terminal A having the allowable  
delay time 1 and actual delay time 3 and a radio

09565856 100101

terminal B having the allowable delay time 3 and  
actual delay time 4 . According to the radio  
resource allocating method, since a delay time  
difference of the radio terminal A between the  
5 allowable delay time and the actual delay time is  
greater than that of the radio terminal B even if the  
actual delay time of the radio terminal A is longer  
than that of the radio terminal B, the radio resource  
is allocated to the radio terminal A with higher  
10 priority.

On the other hand, FIG.8 is a flowchart  
for explaining a third radio resource allocating  
process for allocating the radio resource to the  
satisfied radio terminals or communication  
15 connections in an ascending order of a difference  
between the required quality and the actual  
communication quality. First, the resource  
allocation priority ordering part 108 sorts all  
satisfied radio terminals or communication  
20 connections in the ascending order (smaller to  
greater) of a value that deducted the actual  
communication quality from the required quality (step  
601). The sorted order becomes the priority order of  
the radio resource allocation. When the priority  
25 order of the radio resource allocation is determined,  
the resource allocating part 110 determines whether  
or not the radio resource is remaining (step 602).  
When the radio resource is remaining, the remained  
radio resource is allocated to the satisfied radio  
30 terminals or communication connections (step 603).  
On the other hand, when the radio resource is not  
remained, the third radio resource allocating process  
is terminated.

In the satisfied radio terminals or  
35 communication connections that satisfy relative  
required qualities, when the difference between the  
required quality and the actual communication quality

is smaller, the actual communication quality may be degraded less than the required quality with high possibility. Accordingly, by allocating the radio resource in the ascending order (smaller to greater) of the difference between the required quality and the actual communication quality, it is possible to reduce a probability of degrading the communication quality less than the required quality.

FIG.9 is a flowchart for explaining a fourth radio resource allocating process for allocating the radio resource to the unsatisfied radio terminals or communication connections in an descending order of a degradation degree of the actual communication quality to the required quality. First, the resource allocation priority ordering part 108 sorts all unsatisfied radio terminals or communication connections in the descending order (greater to smaller) of a value that deducted the actual communication quality from the required quality and divided by the required quality (step 701). The sorted order becomes the priority order of the radio resource allocation.

When the priority order of the radio resource allocation is determined, the resource allocating part 110 determines whether or not the radio resource is remaining (step 702). When the radio resource is remaining, the remained radio resource is allocated to the unsatisfied radio terminals or communication connections (step 703). On the other hand, when the radio resource is not remained, the fourth radio resource allocating process is terminated. Accordingly, by allocating the radio resource in the descending order (greater to smaller) of the value that deducted the actual communication quality from the required quality and divided by the required quality.

For example, it is assumed that there are

09555555 100104

the radio terminal A having the allowable delay time 1 and actual delay time 2 and the radio terminal B having the allowable delay time 1000 and actual delay time 1020 . According to the radio resource allocating method shown in FIG.9, differences between the required quality (allowable delay time) and the actual delay time (actual communication quality) of the terminals A and B are 1 and 20 [sec], respectively, and then ratios to the required qualities of the terminals A and B are 100 [%] and 2 [%]. Consequently, the radio resource is allocated to the terminal A with high priority.

On the other hand, FIG.10 is a flowchart for explaining a fifth radio resource allocating process for allocating the radio resource to the satisfied radio terminals or communication connections in an ascending order of a favorable degree of the actual communication quality to the required quality. In this case, the resource allocation priority ordering part 108 sorts all satisfied radio terminals or communication connections in the ascending order (smaller to greater) of a value that deducted the actual communication quality from the required quality and divided by the required quality (step 801). The sorted order becomes the priority order of the radio resource allocation. When the priority order of the radio resource allocation is determined, the resource allocating part 110 determines whether or not the radio resource is remaining (step 802). When the radio resource is remaining, the remained radio resource is allocated to the satisfied radio terminals or communication connections (step 803). On the other hand, when the radio resource is not remained, the fifth radio resource allocating process is terminated.

In the satisfied radio terminals or

09965856 100401

communication connections that satisfy respective required qualities, when the favorable degree of the actual communication quality to the required quality is smaller, the actual communication quality may be degraded less than the required quality with high possibility. Accordingly, by allocating the radio resource in the ascending order (smaller to greater) of the difference between the required quality and the actual communication quality, it is possible to reduce a probability of degrading the communication quality less than the required quality.

However, in a case in which one radio base station 1 manages the plurality of the radio terminals 10 through 40, all radio terminals or communication connections do not have respective required qualities. There may be some radio terminals that do not have respective required qualities (hereinafter called quality-not-required radio terminals). A sixth radio resource allocating process in this case will now be explained in accordance with a flowchart shown in FIG.11.

In this case, the radio resource is allocated to the radio terminals or communication connections that have respective required quality (hereinafter called quality-required radio terminals or communication connections) (step 901). Subsequently, it is determined whether or not the radio resource is remaining (step 902). When the radio resource is remaining, the radio resource is allocated to the quality-not-required radio terminals or communication connections. That is, any one of radio resource allocation processes shown in FIG.5 through FIG.10 is conducted to the quality-required radio terminals or communication connections only. On the other hand, when the radio resource is not remained, the sixth radio resource allocating process is terminated.

09965855-100104

The radio resource allocating processes shown in FIG.5 through FIG.11 are terminated when the radio resource is sufficiently allocated to all radio terminals or communication connections, or when an entire usable radio resource is allocated to the radio terminals or communication connections.

In the radio resource allocating processes as described above, the required quality is the allowable delay time, the transmission rate, the throughput or the like. Details in cases in which the required quality is the allowable delay time and the throughput will now be described.

In one case in which the required quality is the allowable delay time, an actual delay time is measured by a buffer of the sender side. In this embodiment, a transmission delay time on a radio link session (between one radio base station and one radio terminal) will be mainly exemplified as the delay time. The larger delay time, the more the communication quality deteriorates. Accordingly, in FIG.5, when the actual delay time of the radio terminal or communication connection is greater than the allowable delay time, the radio terminal or communication connection does not satisfy the required quality. Thus, in FIG.6, the radio resource is allocated to the radio terminals or communication connections in the descending order of the actual delay time with priority. In FIG.7 through FIG.10, an absolute difference between the allowable delay time and the actual delay time can be applied as the difference between the required quality and the actual communication quality.

That is, when  $D > D_{th}$  where  $D_{th}$  denotes the allowable delay time and  $D$  denotes an average actual delay time for a observation section  $T$ , the required quality is not satisfied. In the first radio resource allocating process in FIG.6, the radio

resource is allocated in a descending order of the actual delay time  $D$ . In the second radio resource allocating process in FIG.7, the radio resource is allocated in a descending order of an absolute value  $|D-D_{th}|$ . In the fourth radio resource allocating process in FIG.9, the radio resource is allocated in a descending order of a value  $|D-D_{th}|/D_{th}$ . On the other hand, when  $D < D_{th}$ , the required quality is satisfied. In the first radio resource allocating process in FIG.6, the radio resource is allocated in a descending order of the actual delay time  $D$ . In the third radio resource allocating process in FIG.8, the radio resource is allocated in an ascending order of an absolute value  $|D-D_{th}|$ . In the fifth radio resource allocating process in FIG.10, the radio resource is allocated in an ascending order of a value  $|D-D_{th}|/D_{th}$ .

Alternatively, when the required quality is the throughput, it is necessary to count an information amount correctly received by a receiver side so as to calculate an actual throughput. A throughput calculating method will now be described with computation expressions. In the following computation expressions, an observation section  $T$  [sec] for the throughput, an information amount  $I_c$  correctly received during the observation session  $T$ , a throughput  $S_{th}$  [bps] required by a certain radio resource or the communication connection, and an actual throughput  $S$  [bps] during the observation section  $T$  are used.

First, in a case in which the certain radio terminal transmits information  $I$  during the observation section  $T$  [sec], the throughput  $S_{th}$  required by the certain radio terminal of communication connection satisfies the following computation expression:

$$S_{th} = I/T.$$

That is, the certain radio terminal or communication connection requires an average of an information transmission rate during the observation section T as the throughput. On the other hand, the actual  
5 throughput satisfies the following computation expression:

$$S = I_c/T.$$

In practice, the actual throughput is calculated as the number of packets correctly received during a  
10 unit time or the observation section T. The lower the throughput, the more the communication quality degrades. Accordingly, in FIG.5, when the actual throughput of the radio terminal or communication connection is lower than the required throughput, the  
15 radio terminal or communication connection does not satisfy the required quality. In FIG.6, the priority of the radio resource is determined in the ascending order of the actual throughput. In FIG.7 through FIG.10, an absolute difference between the required  
20 throughput and the actual throughput can be applied as the difference between the required quality and the actual communication quality.

That is, when  $S < S_{th}$ , the required quality is not satisfied. In this case, in the  
25 second radio resource allocating process in FIG.7, the radio resource is allocated in a descending order of an absolute value  $|S_{th}-S|$ . In the fourth radio resource allocating process in FIG.9, the radio resource is allocated in a descending order of a  
30 value  $|S_{th}-S|/S_{th}$ . On the other hand, when  $S < S_{th}$ , the required quality is satisfied. In the first radio resource allocating process in FIG.6, the radio resource is allocated in an ascending order of the actual throughput S. In the third radio resource  
35 allocating process in FIG.8, the radio resource is allocated in an ascending order of an absolute value  $|S_{th}-S|$ . In the fifth radio resource allocating

00965856 100101

process in FIG.10, the radio resource is allocated in an ascending order of a value  $|S_{th}-S|/S_{th}$ .

In a case in which the required quality is the allowable delay time or throughput, a priority order determining process for the radio resource allocation will now be described in details.

In FIG.12, the allowable delay time  $D_{th}$  and the actual delay time  $D$  are shown for radio terminals A through H in a case in which the required quality is the allowable delay time. The absolute value  $|D-D_{th}|$  of a difference between the actual delay time  $D$  and the allowable delay time  $D_{th}$ , and a rate  $|D-D_{th}|/D_{th}$  of the absolute value  $|D-D_{th}|$  of the difference between the actual delay time  $D$  and allowable delay time  $D_{th}$  are shown in FIG.12.

Referring to FIG.12, delay time states in the radio terminals B, C, D and G (rows without shadows in FIG.13) show  $D > D_{th}$ . Thus, the respective required qualities are not satisfied. Accordingly, by using the radio resource allocating method of FIG.5, the radio resource is allocated to the radio terminals B, C, D and G with higher priority than the radio terminals A, E, F and H. Also, by using the first radio resource allocating method in FIG.6 for the unsatisfied radio terminals B, C, D and G that do not satisfy the relative request qualities, the radio resource is allocated in the descending order of the delay time  $D$ , that is, in an order of the radio terminals C, B, G and D. Alternatively, by using the second radio resource allocating method in FIG.7 for the unsatisfied radio terminals B, C, D and G, the radio resource is allocated in the descending order of the absolute value  $|D-D_{th}|$  of difference between the actual delay time  $D$  and the allowable delay time  $D_{th}$ , that is, in an order of the radio terminals B, C, G and D. By using the fourth radio resource allocating method in

FIG.9 for the unsatisfied radio terminals B, C, D and G, the radio resource is allocated in the descending order of the rate  $|D-D_{th}|/D_{th}$  of the absolute value  $|D-D_{th}|$  of the difference between the actual delay time D and the allowable delay time  $D_{th}$ , to the allowable delay time  $D_{th}$ , that is, in an order of the terminals D, B, G and C.

When the radio resource is allocated to the unsatisfied radio terminals B, C, D and G, the radio resource is allocated to remaining radio terminals, that is, the satisfied radio terminals A, E, F and H that satisfy the respective required qualities (rows with shadows in FIG.13). By using the radio resource allocating method in FIG.6 for the satisfied radio terminals A, E, F and H, the radio resource is allocated in the descending order of the actual delay time D, that is, in an order of the satisfied radio terminals F, A, H and E. Also, by using the third radio resource allocating method in FIG.8, the radio resource is allocated in the ascending order of the absolute value  $|D-D_{th}|$  of the difference between the actual delay time D and the allowable delay time  $D_{th}$ , that is, in an order of the radio terminals H, E, A and F. Alternatively, by using the fifth radio resource allocating method in FIG.10, the radio resource is allocated in the ascending order of the rate  $|D-D_{th}|/D_{th}$  of the absolute value  $|D-D_{th}|$  of the difference between the actual delay time D and the allowable delay time  $D_{th}$ , that is, in an order of the radio terminals H, E, A and F.

Consequently, when the radio resource allocating method in FIG.6 is used for all radio terminals A through H, the radio resource is allocated in an order of the radio terminals C, B, G, D, F, A, H and E. When the second and third radio resource allocating methods in FIG.7 and FIG.8, the

radio resource is allocated in an order of the radio terminals B, C, G, D, H, E, A and F. When the fourth and fifth radio resource allocating methods in FIG.9 and FIG.10, the radio resource is allocated in an

5 order of the radio terminals D, B, G, C, H, E, A and F. Accordingly, the priority order is changed based on a prioritizing criterion. In FIG.12, for example, it is thought that the radio terminal C can be used for the data communication, and thus, a requirement

10 for the delay time is generous. On the other hand, a requirement for the delay time of the radio terminal D is intense. When the delay time is considered, it is preferable to allocate the radio resource to the terminal D, which the required delay time is intense

15 more than the terminal C, with higher priority. Therefore, it is preferable to consider not only the actual delay time and but also the difference degree between the actual communication quality and the required quality.

20 On the other hand, in FIG.14, the required throughput  $S_{th}$  and the actual throughput  $S$  for each of the radio terminals A through H are shown in a case in which the required quality is the throughput. Also, the absolute value  $|S_{th}-S|$  of the difference

25 between the required throughput  $S_{th}$  and the actual throughput  $S$ , the rate  $|S_{th}-S|/S_{th}$  of the absolute value  $|S_{th}-S|$  of the difference between the required throughput  $S_{th}$  and the actual throughput  $S$  to the required throughput  $S_{th}$  are shown in FIG.14.

30 Referring to FIG.14, throughput states in the radio terminals A, B, C, F and H (rows without shadows in FIG.15) show  $S < S_{th}$ . Accordingly, by using the radio resource allocating method of FIG.5, the radio resource is allocated to the radio

35 terminals A, B, C, F and H with higher priority than the radio terminals D, E and G. Also, by using the first radio resource allocating method in FIG.6 for

the unsatisfied radio terminals A, B, C, F and H that do not satisfy the relative request qualities, the radio resource is allocated in the ascending order of the actual throughput S, that is, in an order of the radio terminals H, C, A, B and F. Alternatively, by using the second radio resource allocating method in FIG.7, the radio resource is allocated in the descending order of the absolute value  $|S_{th}-S|$  of difference between the required throughput  $S_{th}$  and the actual throughput S, that is, in an order of the radio terminals F, B, A, H and C. By using the fourth radio resource allocating method in FIG.9, the radio resource is allocated in the descending order of the rate  $|S_{th}-S|/S_{th}$  of the absolute value  $|S_{th}-S|$  of the difference between the required throughput  $S_{th}$  and the actual throughput S, to the required throughput  $S_{th}$ , that is, in an order of the terminals H, B, F, A and C.

When the radio resource is allocated to the unsatisfied radio terminals A, B, C, F and H, the radio resource is allocated to remaining radio terminals, that is, the satisfied radio terminals D, E and G that satisfy the respective required qualities (rows with shadows in FIG.15). By using the radio resource allocating method in FIG.6 for the satisfied radio terminals D, E and G, the radio resource is allocated in the ascending order of the actual throughput S, that is, in an order of the satisfied radio terminals D, E and G. Also, by using the third radio resource allocating method in FIG.8, the radio resource is allocated in the ascending order of the absolute value  $|S_{th}-S|$  of the difference between the required throughput  $S_{th}$  and the actual throughput S, that is, in an order of the radio terminals E, D and G. Alternatively, by using the fifth radio resource allocating method in FIG.10, the radio resource is allocated in the ascending order of

the rate  $|S_{th}-S|/S_{th}$  of the absolute value  $|S_{th}-S|$  of the difference between the required throughput  $S_{th}$  and the actual throughput  $S$ , that is, in an order of the radio terminals G, E and D.

5                   Consequently, when the radio resource allocating method in FIG.6 is used for all radio terminals A through H, the radio resource is allocated in an order of the radio terminals H, C, A, B, F, D, E and G. When the second and third radio  
10 resource allocating methods in FIG.7 and FIG.8, the radio resource is allocated in an order of the radio terminals F, B, A, H, C, E, D and G. When the fourth and fifth radio resource allocating methods in FIG.9 and FIG.10, the radio resource is allocated in an  
15 order of the radio terminals H, B, F, A, C, G, E and D. Accordingly, similarly to the case in which the required quality is the allowable delay time, the priority order is changed based on a prioritizing criterion.

20                   In any one of the priority order determining processes for the radio resource allocation described above, each single frame or each unit of several frames is processed. It is thought that the shorter a process period, the better a  
25 system feature. However, the priority order determining processes become complicated. An optimal process period may be determined in a system design stage. It should be noted that a time required for one frame is needed so that signals from all radio  
30 terminals managed by the radio base station reach to the radio base station. Thus, a time period for one frame is required at the minimum.

                  In the conventional radio communication system, since the communication quality is almost  
35 evenly provided to each radio terminal or each communication connection, only fairness between the radio terminals or communication connections was

09965856 "100101"

considered. However, the multimedia radio communication system represented in FIG.3, it is required to satisfy a different required quality for each radio terminal or communication connection in order to provide a service. In this case, there are radio terminals or communication connections that intensely require the communication qualities, and radio terminals or communication connection that generously require the communication qualities. In such this system, in this embodiment described above, the priority order for the radio resource allocation is determined based on the required quality of each radio terminal or communication connection. Therefore, it is possible to increase the number of radio terminals or communication connections that satisfy the relative required qualities.

The present invention is not limited to the specifically disclosed embodiments, variations and modifications, and other variations and modifications may be made without departing from the scope of the present invention.

The present application is based on Japanese Priority Application No.2000-302637 filed on October 2, 2000, the entire contents of which are hereby incorporated by reference.

09965855-100101